

**SELECT FIRST MACHINE/LANGUAGE:**

**E260Eco-ENG**

**Updates only to columns I-V**

Last update 14.3.2014

**TANA E260Eco SANITARY LANDFILL COMPACTOR**

**Technical specification E260-D102624 14.3.2014**

**GENERAL INFORMATION AND MAIN DIMENSIONS**

	SI	US	
Weight	26000 kg	57320 lb	
Total length	8260 mm	27 ft	1 in
Total width (with dozer blade)	3660 mm	12 ft	
Total height	4320 mm	14 ft	2 in
Wheelbase	4050 mm	13 ft	3 in
Ground clearance	890 mm	2 ft	11 in
Length without dozer blade	6640 mm	21 ft	9 in
Width without dozer blade	3250 mm	10 ft	8 in
Dozer blade width	3660 mm	12 ft	
Dozer blade height	1750 mm	5 ft	9 in
Inside turning radius	3880 mm	12 ft	9 in
Driving speed ranges	0...4,5 km/h	0...2,8 mph	
	0...6 km/h	0...3,7 mph	
Max crushing force	127 kN	28551 lbf	
Max operating altitude	1000 m	3281 ft	
Ambient operating temperature	-30 °C...+50 °C		
Exhaust emissions	Fulfills U.S. EPA Tier 4(f), CARB Tier 4 and EU Stage IV		
Noise emissions	Fulfills EU directive 2000/14/EC		
Warranty	Basic warranty 12 months/2000 operating hours		

**COMPACTION DRUMS**

Uniform full-width drums with forged crushing teeth made of wear resistant steel. Adjustable, forged wear-resistant steel scraper bars on both sides of the drums. Adjustable, wear resistant steel wire cutters in the ends of drums.

	SI	US	
Crushing/compaction width, front drum	2660 mm	8 ft	9 in
Crushing/compaction width, rear drum	2660 mm	8 ft	9 in
Diameter including crushing feet	1620 mm	5 ft	4 in
Height of crushing feet	200 mm		8 in
Number of crushing feet, pcs (front+rear)	80+80		
Number of scraper bars, pcs (front+rear)	14+14		
Number of wire cutters, pcs (front+rear)	2+4		

**DOZER BLADE**

Dozer blade is operated with two hydraulic cylinders.

Two arms

	SI	US	
Width	3660 mm	12 ft	
Height	1750 mm	5 ft	9 in
Movement above ground level	1170 mm	3 ft	10 in
Movement below ground level	150 mm		6 in
Upper part of blade: trash screen			
Arm joints with hardened pins and spherical bearings			

**FRAME**

Frame is constructed of two modular drum frames connected together with longitudinal upper frame. The drum frame acts as a shell around the drum, which helps to prevent waste raising to the upper parts of machine from below.

The upper frame is equipped with center point articulation operated with two hydraulic cylinders.

Articulation links are equipped with hardened pins and spherical steel bearings

Angle of articulation left or right 40 degrees

**SERVICE PLATFORMS AND PROTECTION**

Service platforms and steps are equipped with banisters and anti-slide surfaces.

Engine and powerpack are protected with a lockable hood.

**VANDALISM PROTECTION**

Lockable cabin, engine compartment, fuel filler cap and toolbox

Electronic key for ignition

**CABIN EQUIPMENT**

Pressurized, sound and heat insulated cabin

Air suspended seat with head rest

Seat heating

Right hand emergency exit door

Foot support

Inside mirror

Sun cover front

Swivelling operator's seat

Control symbols according to ISO 3767

Lockable door

Cabin lights

Socket for mobile phone re-charge

External rear view mirrors

Shelf and lockers

Front and rear windshield intermittent wipers and washers

Heater and AC unit

Replaceable cabin air filters in accordance with EUROVENT

Radio and CD/MP3-player

EUROVENT -4/5 "Method of testing air filters used in general ventilation"

**TOTAL CONTROL SYSTEM**

Decentralised electronic total control system. Different modules are interconnected via a CAN bus.

**TANA ProTrack®**

Wireless TANA ProTrack® connection to TANA Control System through Internet.

**CONTROL SYSTEM DISPLAY**

LCD 5,7" colour display mounted on the right hand side of operator. All gauge and monitor functions shown on the display.

**MAIN DISPLAY**

- Diesel engine charge pressure
- Engine oil pressure
- Engine oil temperature
- Engine intake air temperature
- Engine coolant temperature
- Hydraulic oil temperature
- Gear box temperatures
- Fuel level
- Fuel consumption
- Charging voltage
- Engine RPM
- Engine load percentage
- Engine operating hours
- Urea level

**CONTROL SYSTEM WARNINGS AND ALARMS**

- Total amount of warnings and alarms over 500 pcs. For example:
- Engine over speed
- Engine air filter contamination
- Hydraulic oil temperature (both high and low)
- Low hydraulic oil level
- Fuel level
- Gearbox temperatures (both high and low)
- Hydraulic oil return line filter clogging
- Drive hydraulics charge pressure filter clogging
- Low transmission charge pressure
- Voltage (both high and low)
- All diesel engine alarms shown on display (e.g. oil pressure, coolant temperature etc.)

**CONTROLS**

- Transmission and parking brake on/off
- Headlights
- Additional lights
- Warning light
- Mirror heater
- Seat heater
- Windshield wipers and washers
- Horn
- Speed range control
- Emergency stop
- Start-stop switch: power on/off, start
- Multi-selector switch: windshield wiper speed, air conditioning/heater control

**CONTROL LEVERS**

Control of driving and dozer blade movements by two joysticks/levers. Joysticks integrated in armrests on both sides of the operator's seat.

The control levers return automatically into neutral position when released and the movements of the machine cease.

Left hand joystick: control of driving speed & direction,braking, speed range selection with a button

Right hand joystick: steering and dozer blade control, bucket control (option, models E260 Eco - E380 Eco), horn

<b>ROPS/FOPS</b>	
ROPS in accordance with ISO 3471:2008	
FOPS in accordance with ISO 3449:2005	

<b>ENGINE</b>	
Cummins QSL9-C265	
6-cylinder, in-line, water-cooled, turbo-charged, after-cooled, four-stroke diesel engine.	
Electronic engine control system which communicates with compactor's TCS-control system through CAN-bus.	
<b>Engine performance data in accordance with SAE J1995:</b>	
Maximum power	265 BHP(198kW)@2000 RPM
Maximum torque	1119 Nm(825lb-ft)@1400 RPM
Power rating	265 BHP(198kW)@2000 RPM

<b>ENGINE EQUIPMENT</b>	
Attachment to the frame with vibration and noise damping rubber mounts.	
Dry-type air cleaner with replaceable primary and safety element. Inbuilt pre-cleaner and service indicator.	
Fuel filter and water separator	
Oil filter	
Radiator + separate charge air cooler	
Aftertreatment system	

<b>POWER TRANSMISSION</b>	
Closed circuit hydrostatic transmission	
Separate systems for both drums	
Control of driving speed and direction with one lever	
Stepless control of speed	
Two driving speed ranges	
<b>Pumps:</b>	
One tandem pump	
Variable displacement axial piston pumps with electrical proportional control	
<b>Motors:</b>	
Variable displacement motors	2 pcs
<b>Cooling of hydraulic system:</b>	
Air operated oil cooler	
Removable air filtration screen	
<b>Hydraulic oil filtration:</b>	
Return line filter	
Two charge pressure filters	
Hydraulic oil filling filter	

<b>FINAL DRIVES</b>		
Transmit power of the hydraulic motors to the drums		
Three-stage planetary gear	2 pcs	
	SI	US
Cooling water volume per gear	230 l	61 gal
Integrated spring applied, hydraulically released multi-plate parking brake		
Splash lubrication system		

**BRAKES**

Service brakes: Hydrostatic transmission acts as service brakes, separate circuits for both drums

Parking/Emergency brakes: spring applied, hydraulically released multi-plate parking brake integrated in planetary gear boxes

**AUXILIARY HYDRAULICS**

Open circuit system with electro-hydraulic load sensing (LS) control.

Variable displacement axial piston pump.

Directional control valve with electro hydraulic proportional control

**HYDRAULIC OIL TANK**

Hydraulic oil tank is located inside the engine hood.

Level sensor with alarm

Breather filter

**FUEL TANK**

Tank is located inside the upper frame under operator cabin.

Lockable filling cap

Service hatch

Suction strainer

Drain cock

Capacity 760 l (201 US gal)

Level sensor with alarm

**UREA TANK**

Tank is located inside the rear frame

Suction strainer

Capacity 56 l (15 US gal)

Level sensor with alarm

**ELECTRICAL EQUIPMENT**

24 VDC system

Batteries 12 V 170 Ah, 2 pcs

Circuit breaker

Lights: front 4 pcs, rear 4 pcs

Horn

Voltage reducer for radio

Socket for hand light in engine compartment

Back up alarm

**LITERATURE**

**MANUALS**

TANA – operation manual

TANA – service & maintenance manual

TANA – spare parts manual

Weights and measurements are given within normal tolerances. Manufacturer reserves the right to alter the above as necessary.