

**TANA SHARK 440Deco SHREDDER**  
**Technical specification 440Deco-D101437C 15.9.2015**

**GENERAL**

Single rotor slow speed shredder
Build on semi trailer chassis
Powered by diesel engine
Hydrostatic shredding rotor transmission
Suitable for large variety of different materials and fractions
Controlled by electronic Tana Control System (TCS)
Left side counter wall is operated with hydraulic cylinder in order to remove unsuitable materials from the rotor area
Rotor knives and counter knives can be serviced when the counter wall is opened

**MAIN DIMENSIONS**

	SI	US	
Weight	25600 kg	56400 lb	
Total length in operation	15750 mm	51 ft	8 in
Total length in transportation	10530 mm	34 ft	6 in
Total width	2520 mm	8 ft	3 in
Total height in operation	4030 mm	13 ft	3 in
Total height in transportation	3880 mm	12 ft	9 in
Height of the fifth wheel coupling	1270 mm	4 ft	2 in
Feeding height	3400 mm	11 ft	2 in
Powerpack length			
Powerpack width			
Powerpack height			
Ambient operating temperature	-30 °C...+45 °C		
Exhaust emissions	Fulfills U.S. EPA Tier 4 final, CARB Tier 4 final and EU Stage IV		
Warranty	Basic warranty 12 months/1500 operating hours		
Noise emissions	Lwa 116 dB (ISO3744:2010)		

**SHREDDING TOOLS**

	SI	US	
Rotor shredding length	3000 mm	9 ft	10 in
Rotor diameter	920 mm	3 ft	
Nominal rotor torque	440 kNm		
Rotor speed	0-28 rpm		
Turnable, bolt-on rotor knives with two wearing surfaces			
Number of rotor knives	33 pcs		
Turnable, drop-in counter knives with two wearing surfaces			
Number of counter knives	23 pcs		

<b>DIESEL ENGINE</b>
Cummins QSX15, Tier 4 final (EU stage IV)
6-cylinder, in-line, water-cooled, turbo-charged, after-cooled, four-stroke diesel engine. Displacement 15 liters.
Electronic engine control system which communicates with shredder's TCS-control system through CAN-bus.
Power rating 399 kW (535 bhp)@2100 rpm, SAEJ1995
Maximum power 433 kW (580 bhp)@1800 rpm, SAEJ1995
Maximum torque 2644 Nm (1950 lb-ft)@1400 rpm, SAEJ1995
Dry type air cleaner with replaceable primary and safety element. In built pre-cleaner and service indicator.
Fuel coarse and fine filter, water separator
Oil filter, coolant filter
Radiator + separate charge air cooler
Exhaust aftertreatment device

<b>POWER TRANSMISSION</b>
Closed circuit hydrostatic transmission
Continuously variable and automatic rotor speed control
Allows direction of rotor rotation in both directions
Variable displacement axial piston pumps with electrical control
Hydraulic motors with planetary gears in both ends of shredding rotor
Air operated oil cooler
Return line filter and two charge pressure filters with electrical indication
Pressurized planetary gear lubrication

<b>AUXILIARY HYDRAULICS</b>
Open circuit system
Electro-hydraulic control
Used for counter wall open/close, conveyor drive, conveyor tilt, overband magnet drive and overband magnet height control

<b>UREAN TANK</b>
Suction stainer
Capacity 56 l (15 US gal)
Level sensor with alarm

<b>HYDRAULIC OIL TANK</b>
Hydraulic oil tank is located inside the engine hood.
Automatic oil level monitoring system
Breather filter

<b>CONTROL SYSTEM (TCS)</b>
Electronic control system
CAN-bus communication between control modules
Operational switch panel with colour display
USB-connection for software updates etc.
Remote control (Option)

<b>ELECTRICAL EQUIPMENT</b>	
24 VDC system	
Batteries 12 V 180 Ah, 2 pcs	
Circuit breaker	
Socket for hand light in engine compartment	

<b>PRO TRACK</b>	
Wireless ProTrack connection to TANA Control System information through Internet	

<b>SEMI-TRAILER</b>	
EC – Whole Vehicle Type Approval: 2007/46EC – EC-WVTA / Comission regulation 371/2010	
Bogie axles with leaf spring suspension	
Max towing speed 100 km/h (Check local laws)	
Pneumatic brake system with ABS	
Equipped with manual support legs (std) or hydraulic support legs (option)	

<b>DISCHARGE CONVEYOR</b>			
	SI	US	
Discharge height	4030 mm	13 ft	3 in
Belt width	1030 mm	3 ft	5 in
Hydrostatic drive			
Adjustable belt speed			

<b>SCREEN SYSTEM (optional)</b>	
Shredder can be equipped with under rotor screen	
Size of end product can be easily calibrated by using proper size of screen	
Mesh sizes 109 - 275 mm	

<b>OVERBAND MAGNET (optional)</b>	
Permanent type magnet	
Hydrostatic drive	

<b>TOOLS AND PARTS</b>	
Hand tool kit	
Tools for wear part care	
Filters to be changed after the first 50 operating hours	

<b>LITERATURE</b>	
<b>MANUALS</b>	
TANA – operation manual	
TANA – service & maintenance manual	
TANA – spare parts manual	
Weights and measurements are given within normal tolerances. Manufacturer reserves the right to alter the above as necessary.	